UNIVERSAL MOUNT FAN COIL - COOLING ONLY

Cooling for limited area applications

R-410A AND R22 REFRIGERANTS







Lennox delivers convenient comfort all year

The Universal Mount Fan Coil from Lennox provides exceptional cooling that is ideal for limited-area applications. Its modern and elegant appearance can easily accommodate design considerations and the LED display makes it user-friendly for precise comfort control. With a flexible drainpipe design, the unit is designed for ceiling and floor installations.

Features for efficient operation and long-term reliability

Auto restart restores programmed settings in the event of a power outage.

Sleep mode prevents overheating or overcooling at night, for sound sleep.

Self-diagnosis displays error codes when a fault is detected, simplifying maintenance and repair.

On/off timer allows the unit to be turned on or off automatically in schedules of up to 12 hours.

R-410A or R22 refrigerant available for added flexibility.

Models and performance specifications

	MODEL #	Voltage	Nominal Cooling [Btu/H]	Packing Dimension W x D x H [mm]	Gross Weight [kg]	Refrigerant Type	Air Flow (H/M/L) [M³/H]	Noise Rating (H/M/L) [db]
AIR CONDITIONER	LXGUCMD036100P20-3	220~230-1-60	36,000	1,360 x 755 x 313	37.5	R22 or R-410A	1,900/1,700/1,500	53/50/47
	LXGUCMD048100P20-3	220~230-1-60	48,000	1,360 x 755 x 313	39	R22 or R-410A	2,000/1,700/1,500	51/48/45
	LXGUCMD060100P20-3	220~230-1-60	60,000	1,725 x 755 x 313	45	R22 or R-410A	2,500/2,100/1,800	56/52/48

Note: Due to Lennox' ongoing commitment to quality, all specifications, ratings and dimensions are subject to change without notice.







Visit us at www.lennox.com, or contact us at 1-877-726-0024.